

Paraterm bar nailed 8" O.C.
with cant of Vulkem 116 or
Dymonic 100

Lagging, treated exterior grade
Plywood or Cement Board

Paraseal LG bentonite side
up.

Optional: Permaquik 200
crystalline coating

2" Sand slurry protection slab (required
for slabs greater than 6" thick)

12" X 12" Paraseal LG corner strip with
bentonite side up

Compacted base, soil or 2" Sand slurry mud slab

Floor slab

The vertical to horizontal
transition shall be cut to a
45 degree angle

Paraseal LG with bentonite
side against concrete.

Superstop Waterstop
at all cold joints

Wide crown staple

NOTE: Paraseal products require a min of 24 PSF of compaction/confinement in order to function as designed.

TREMCO

www.tremcosealants.com

3735 Green Road * Beachwood, OH 44122
Phone : 866-209-2404 * Fax: 216-766-5535

Detail: CAST IN PLACE ELEVATOR, SUMP OR PIT WITH SHORING
(BENTONITE SIDE UP) (NON-SUBMERGED)

This detail is intended for conceptual purposes only.

Drawn by: MI

Checked by: JM

Scale: None

Sheet Number:

Date: 5/24/2016

File Name:

B-BSOG-10-LG20

Rev #

00