



- NOTE: Sand slurry protection slab and mud slab are recommended for heavily reinforced slabs greater than 6" thick that are to be placed on damp or unstable earth.
- NOTE: Paraseal products require a min of 24 PSF of compaction/confinement in order to function as designed.
- NOTE: Not recommended for use in submerged conditions.
- NOTE: When pouring concrete over the Paraseal LG pour either directly on top of the seam or towards the closed edge of the seam so as not to dislodge the seam and/or allow concrete between the lapped seam.
- NOTE: Refer to detail PE-BSOG-03-LG20
- NOTE: If Mud Slab is not placed refrain from using chipped aggregate.

<b>TREMCO</b> <small>www.tremcosealants.com</small> <small>3735 Green Road * Beachwood, OH 44122</small> <small>Phone : 866-209-2404 * Fax: 216-766-5535</small>	Detail: <b>BSOG TYPICAL SEAM DETAIL (HDPE SIDE UP) - (NON-SUBMERGED)</b>	Sheet Number:	File Name:	Rev #
	<small>This detail is intended for conceptual purposes only.</small>	Drawn by: <b>MI</b> Checked by: <b>JM</b> Scale: <b>None</b>	Date: <b>5/24/2016</b>	<b>PE-BSOG-06-LG20</b>