



- Paraseal LG with bentonite side facing concrete
- Superstop Waterstop; Install 2" from outer wall
- 1" x 1" (25mm x 25mm) Paragranular Pocket
- Protection Slab
- TREMproof 260 at 100 wet mils
- Paraseal LG with bentonite side up
- Permanent Seam Tape
- Compacted Earth base min. 85 proctor
- Paraseal LG with bentonite side up

Permanent Seam Tape

4" (10 cm)

6" (15 cm)

6" (15 cm)

1" (25 mm)

NOTE: Paraseal products require a min of 24 PSF of compaction/confinement in order to function as designed.  
 NOTE: Not recommended for use in submerged conditions.

**TREMCO**  
 www.tremcosealants.com  
 3735 Green Road \* Beachwood, OH 44122  
 Phone : 866-209-2404 \* Fax: 216-766-5535

Detail: TREMproof TWS - BELOW SLAB ON GRADE AT FOOTING TO BACKFILLED WALL  
 (BENTONITE SIDE UP) (NON-SUBMERGED)  
 This detail is intended for conceptual purposes only. Drawn by: MI Checked by: AC Scale: None

Sheet Number:  
 Date: 5/27/2016

File Name:  
 TWS-BSOG-08

Rev #  
 00